

Venom-R

- Sizes to fit custom bikes
- Low noise levels
- Robust radial construction to cope with heavy loads
- Good stability in corners



Venom-R

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
Venom-R AM42 Rear									
90000001214	4953913	180/55R18	74V	MT5.50	5.50 - 6.00	177 / 7.0	662 / 26.1	7.0	500 / 800.3
90000001215	4955413	330/30R17	87V	MT12.00	11.00 - 12.25	330 / 12.9	634 / 25.0	6.5	522 / 835.6

Venom

- Low noise levels
- Excellent cornering stability
- Reinforced fitments available for bikes carrying heavy loads



Venom

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
Venom AM41 Front									
90000000762	2808012	80/90-21	48H	MT1.85	1.60 - 2.15	83 / 3.3	688 / 27.1	5.2	479 / 766.4
90000000763	2808112	90/90-21	54H	MT2.15	1.85 - 2.50	94 / 3.7	701 / 27.6	5.2	468 / 748.8
90000000760	2806912	100/90-18	56H	MT2.50	2.15 - 2.75	107 / 4.2	638 / 25.1	5.2	520 / 832.0
90000000768	2809612	110/90-19	62H	MT2.50	2.15 - 3.00	119 / 4.7	682 / 26.9	5.2	487 / 779.2
90000000758	2806012	120/90-18*	71H	MT2.75	2.50 - 3.00	129 / 5.1	674 / 26.5	5.2	496 / 793.6
90000000753	2800091	120/70-21*	68H	MT3.50	2.75 - 3.75	120 / 4.7	709 / 27.9	4.8	467 / 747.3
90000000759	2806612	130/70B18*	69H	MT3.50	3.00 - 4.00	130 / 5.1	647 / 25.5	4.7	513 / 820.8
90000000769	2809713	140/70B18	67V	MT3.75	3.50 - 4.50	139 / 5.5	658 / 25.9	4.7	503 / 805.2
90000000761	2807412	150/80-16	71H	MT3.50	3.00 - 4.25	157 / 6.2	637 / 25.1	5.2	525 / 840.0
Venom AM42 Rear									
90000000775	2844412	140/90-15*	76H	MT3.50	2.75 - 3.75	149 / 5.9	633 / 24.9	8.7	530 / 848.0
90000000789	2848912	150/90B15*	80H	MT3.50	3.00 - 4.25	159 / 6.3	645 / 25.4	8.7	523 / 836.8
90000000790	2848913	150/90VB15 (74V)	74V	MT3.50	3.00 - 4.25	159 / 6.3	645 / 25.4	8.7	523 / 836.8
90000000799	2950091	150/70B18*	76V	MT4.25	3.50 - 4.50	148 / 5.8	665 / 26.2	5.7	498 / 796.7
90000000778	2844912	160/80B16*	81H	MT4.00	3.50 - 4.50	167 / 6.6	665 / 26.2	8.7	505 / 808.0
90000000776	2844512	170/80B15*	83H	MT4.00	3.50 - 4.50	176 / 6.9	659 / 25.9	8.7	512 / 819.2
90000000774	2843712	200/70-15	82H	MT5.50	4.75 - 6.25	203 / 8.0	665 / 26.2	7.7	505 / 808.0

AM20/AM21

- Accomplished all-rounder
- Tread pattern designed to give first class water dispersal under the contact patch.



AM20/AM21

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
AM20 Front									
90000000750	2748812	90/90-19	52H	MT2.15	1.85 - 2.50	95 / 3.7	647 / 25.5	5.0	512 / 819.2
90000000749	2748112	90/90-21	54H	MT2.15	1.85 - 2.50	93 / 3.7	700 / 27.6	5.0	474 / 758.4
90000000748	2745012	130/90-16*	73H	3.00D	2.50 - 3.50	138 / 5.4	638 / 25.1	5.0	525 / 840.0
AM21 Rear									
90000000751	2755019	MT90-16*	74H	3.00D	2.50 - 3.50	139 / 5.5	650 / 25.6	7.8	517 / 827.2
90000000752	2759012	230/60B15	86H	MT6.25	5.50 - 7.00	230 / 9.1	658 / 25.9	8.6	508 / 812.8

*Reinforced | MT90-16 equivalent to 130/90-16