

Roadrider

- Covers a large range of bikes
- Large contact patch for excellent grip at all lean angles
- Comprehensive range of sizes – from modern to more traditional
- Performance upgrade for classic and vintage motorcycles



Roadrider

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
Roadrider AM26 Front									
90000000660	2268813	90/90-19	52V	MT2.15	1.85 - 2.50	99 / 3.9	647 / 25.5	5.0	512 / 818.9
90000000657	2268113	90/90-21	54V	MT2.15	1.85 - 2.50	98 / 3.9	698 / 27.5	5.0	474 / 759.0
90000000652	2260213	100/80-17	52V	MT2.50	2.15 - 2.75	101 / 4.0	595 / 23.4	5.0	557 / 890.4
90000000658	2268213	110/90V16	(59V)	MT2.50	2.15 - 3.00	117 / 4.6	603 / 23.7	5.0	549 / 878.6
90000000653	2265213	110/70V17	(54V)	MT3.00	2.50 - 3.50	108 / 4.3	593 / 23.3	5.0	558 / 893.4
90000000654	2265513	110/80V17	(57V)	MT2.50	2.15 - 3.00	112 / 4.4	614 / 24.2	5.0	539 / 862.9
90000000655	2266113	120/70V17	(58V)	MT3.50	2.75 - 3.75	120 / 4.7	607 / 23.9	5.0	546 / 872.8

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
Roadrider AM26 Rear									
90000000671	2276813	4.00-18	64V	MT2.50	2.15 - 3.00	116 / 4.6	671 / 26.4	7.5	493 / 789.6
90000000676	2279513	120/80-18	62V	MT2.75	2.50 - 3.00	120 / 4.7	652 / 25.7	7.5	508 / 812.6
90000000668	2276013	120/90-18	65V	MT2.75	2.50 - 3.00	129 / 5.1	675 / 26.6	7.5	491 / 784.9
90000000679	2279913	130/70-17	62V	MT3.50	3.00 - 4.00	130 / 5.1	625 / 24.6	7.5	530 / 847.7
90000000670	2276613	130/70V18	(63V)	MT3.50	3.00 - 4.00	133 / 5.2	649 / 25.6	7.5	510 / 816.3
90000000667	2275913	130/80-17	65V	MT3.00	2.50 - 3.50	136 / 5.4	645 / 25.4	7.5	513 / 821.4
90000000678	2279813	130/80V18	(66V)	MT2.75	2.50 - 3.50	137 / 5.4	672 / 26.5	7.5	493 / 788.4
90000000666	2275713	130/90-17	68V	MT3.50	2.50 - 3.50	140 / 5.5	671 / 26.4	7.5	493 / 789.6
90000000673	2277613	140/70-17	66V	MT3.75	3.50 - 4.50	140 / 5.5	641 / 25.2	7.5	517 / 826.5
90000000677	2279713	140/70V18	(67V)	MT3.75	3.50 - 4.50	142 / 5.6	666 / 26.2	7.5	497 / 795.5
90000000665	2275113	150/70V17	(69V)	MT4.25	3.50 - 4.50	156 / 6.1	656 / 25.8	7.5	505 / 807.6
90000000669	2276513	150/70V18	(70V)	MT4.25	3.50 - 4.50	154 / 6.1	679 / 26.7	7.5	488 / 780.3
90000000672	2277413	150/80V16	(71V)	MT3.50	3.00 - 4.25	161 / 6.3	655 / 25.8	7.5	506 / 808.9
90000000662	2270011	160/80-15	74V	MT3.75	3.00 - 4.50	162 / 6.4	637 / 25.1	7.5	520 / 831.7
90000000663	2270313	MT90-16*	(74V)	3.00D	2.50 - 3.50	137 / 5.4	646 / 25.4	7.5	513 / 820.1

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
Roadrider AM26 Universal									
90000000656	2267513	3.25-19	54V	MT2.15	1.85 - 2.50	98 / 3.9	664 / 26.1	5.0	499 / 797.9
90000000661	2269913	90/90-18	51V	MT2.15	1.85 - 2.50	97 / 3.8	619 / 24.4	5.0	535 / 855.9
90000000680	2283013	100/90-18	56V	MT2.50	2.15 - 2.75	108 / 4.3	642 / 25.3	5.6	516 / 825.2
90000000683	2289013	100/90-19	57V	MT2.50	2.15 - 2.75	109 / 4.3	671 / 26.4	5.6	493 / 789.6
90000000684	2289413	110/80V18	(58V)	MT2.50	2.15 - 3.00	111 / 4.4	640 / 25.2	5.6	517 / 827.8
90000000681	2287013	110/90V18	(61V)	MT2.50	2.15 - 3.00	116 / 4.6	663 / 26.1	5.6	499 / 799.1
90000000682	2288413	120/80V16	(60V)	MT2.75	2.50 - 3.00	126 / 5.0	601 / 23.7	5.6	551 / 881.5
90000000664	2274813	120/80-17	61V	MT2.75	2.50 - 3.00	120 / 4.7	629 / 24.8	7.5	526 / 842.3
90000000674	2278613	120/90-17	64V	MT2.75	2.50 - 3.00	128 / 5.0	649 / 25.6	7.5	510 / 816.3
90000000675	2279213	140/80V17	(69V)	MT3.50	2.75 - 3.75	143 / 5.6	665 / 26.2	7.5	498 / 796.7

*Reinforced | MT90-16 equivalent to 130/90-16.