

## Roadrunner (AM9)

- A great value all-rounder
- Can be fitted either to the front or rear of your bike



### Roadrunner AM9

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
<b>Roadrunner AM9 Universal</b>									
90000000599	1607910	<b>4.10-19 TT</b>	61H	2.50	1.85 - 3.00	102 / 4.0	667 / 26.3	7.0	507 / 811.2

## Gangster

- Designed for retro cruisers and customs, it features a 2<sup>3</sup>/<sub>4</sub>" whitewall
- Insures ride and stability
- Can be fitted either to the front or rear of your bike



### Gangster

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
<b>Gangster Universal</b>									
90000000738	2665009	<b>MT90-16**WW</b>	74H	3.00	2.50 - 3.50	140 / 5.5	648 / 25.5	8.2	511 / 817.6

## Speedmaster MKII (AM6)

- Classic ribbed front tyre
- Speed rated to 112 mph/180kmh
- Curved tread profile and ribbed pattern so typical of classic bikes
- Best used in conjunction with the Safety Mileage MKII rear tyre



### Speedmaster MKII AM6

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
<b>Speedmaster AM6</b>									
90000000618	1727410	<b>3.00-19* TT</b>	54S	1.85	1.60 - 2.15	78 / 3.1	641 / 25.2	3.5	517 / 827.2
90000000611	1659401	<b>3.00-21* TT</b>	57S	1.85	1.60 - 2.15	76 / 3.0	691 / 27.2	3.6	481 / 769.6
90000000607	1657501	<b>3.25-19 TT</b>	54S	2.15	1.85 - 2.50	86 / 3.4	658 / 25.9	4.0	497 / 795.2
90000000608	1657601	<b>3.50-19 TT</b>	57S	2.15	1.85 - 2.50	92 / 3.6	682 / 26.9	3.6	482 / 771.2

## Safety Mileage MKII (AM7)

- Classic block pattern rear tyre
- Available in a variety of different tread patterns designed to suit older bikes
- Modern rubber compounds deliver enhanced durability and performance
- Best used in conjunction with the Speedmaster MKII front tyre



### Safety Mileage MKII AM7

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
<b>Safety Mileage MK II AM7</b>									
90000000619	1727610	<b>3.50-19 TT</b>	57S	2.15	1.85 - 2.50	93 / 3.7	682 / 26.9	8.1	482 / 771.2
90000000601	1646801	<b>4.00-18 TT</b>	64S	2.50	2.15 - 3.00	111 / 4.4	677 / 26.7	8.1	488 / 780.8
90000000602	1720011	<b>4.00-19 TT</b>	65H	2.50	2.15 - 3.00	110 / 4.3	702 / 27.6	9.2	471 / 753.6
90000000616	1694901	<b>5.00-16 TT</b>	69S	3.00	3.00 - 3.50	131 / 5.2	669 / 26.3	8.1	499 / 798.4

## Sidecar Triple Duty

- A great all-rounder for every position
- Although especially suited to the front wheel, these tyres can be used in any position on a sidecar outfit



### Sidecar Triple Duty

US Code	European Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
<b>Sidecar Triple Duty</b>									
90000000617	1697605	<b>3.50-19 TT</b>	57L	2.15	1.85 - 2.50	92 / 3.6	679 / 26.7	9.4	491 / 785.6

\*Reinforced | TT = Tube Type | \*\*White Wall | \*\*\*White Wall only